

Speed F2

Merkmaie:

- Mini-Bodenpumpe zur Befestigung am Rahmen
- Herausziehbarer Schlauch.
- Großes Volumen.
- T-Griff, Aluminiumrohr
- Für Schrader, Presta und Dunlop geeignet.
- Aluminiumhebel und Ventilkappe.
- Max. Druck 140 PSI (10 Bar)

Speed F2

Caractéristiques :

- Mini pompe de sol pour fixation sur cadre
- Tuyau extractible
- Haut volume
- Poignée en T, baril en aluminium
- Raccord réversible Schrader, Presta et Dunlop
- Levier en aluminium et bouchon de valve
- Pression max. 140 psi (10 bars)

Speed F2

Características:

- Mini bomba de superficie para fijar en marco
- Manguera extraíble
- Volumen alto
- Asa en T, tambor de aluminio
- Válvula Schrader presta y dunlop
- Palanca de aluminio y tapa de la válvula
- Presión máx. 140 psi (10 bar)

Speed F2

Caratteristiche:

- Mini pompa da pavimento per fissaggio su telaio
- Tubo estraibile
- Volume elevato
- Maniglia a T, serbatoio in allume
- Reversibile schrader presta e dunlop
- Leva in allume e coprialvola
- Pressione massima 140 psi (10 bar)

Speed F2

產品特色:

- 車架固定型的落地式打氣筒
- 隱藏式可伸縮膠管
- 高效率、大氣量
- 握槳式T型手柄、鋁合金氣筒
- 可轉換美式嘴、法式嘴與德式氣嘴
- 鋁合金指壓鎖柄與氣嘴蓋
- 最大壓力140 psi (10 bar)




Push the buttons in both sides of pump head to pull the extractable hose out.



Clip the pump into the bracket and make sure the metal step is fastened down the hook of the bracket.



Go around the pump with the band on the bracket, and then fix the band to the hook of the bracket.



SCHRADER

PRESTA
and
DUNLOP

Speed F2

Features:

- Mini floor pump for fixed on frame
- Extractable hose
- High volume
- T-handle, Alum barrel
- Reversible schrader presta and dunlop
- Alum lever and valve cap
- Max. pressure 140 psi (10 bar)



Pump head attached with extractable hose can protect tyre valve from damage when inflating.