

WWW.AIRACE.COM.TW
AIRACE

AIRACE
WWW.AIRACE.COM.TW

產品特色:

- 附隱藏式膠管的風嘴頭，打氣時可保護輪胎氣嘴不受到損壞
- 鋁合金指壓鎖柄

- 三節疊縮式設計
- 最大壓力100psi (7 bar)
- 超迷你尺寸，易於攜帶
- 防塵蓋

FIT Tele R

Caratteristiche:

- Testa della pompa attaccata con tubo estraibile in grado di proteggere la valvola pneumatica da eventuali danni derivanti dalla dilatazione
- Leva di alluminio
- Design telescopico
- Pressione max 100 psi (7 bar)
- Dimensioni ridotte per un comodo trasporto
- Coperchio antipolvere


FIT Tele R

Leistungsmerkmale:

- Pumpenkopf an ausziehbarem Schlauch befestigt, um das Autoventil beim Aufpumpen vor Schäden zu schützen
- Aluminiumhebel
- Teleskopausführung
- Max. Druck 100 psi (7 Bar)
- Sehr kleines Format für unterwegs
- Staubschutzkappe



Telescope design



SCHRADER
PRESTA and DUNLOP



Quick inflating mode



Valve protect inflating mode



1. Clip the pump into the bracket
2. Go around the pump with the rubber band on the bracket, and then fix the rubber band to the hook of the bracket.


NORMAL

AIRACE
WWW.AIRACE.COM.TW

FIT Tele R

Features:

- Pump head attached with extractable hose which can protect tyre valve from damage when inflating
- Alum lever
- Telescope design
- Max. pressure 100 psi (7 bar)
- Micro size for easy carry
- Dust cap



Pump head attached with extractable hose
can protect tyre valve from damage when inflating

AIRACE



Made in Taiwan